

BLAKES SURFACE CLEANER

67601

Description: BLAKES SURFACE CLEANER is a concentrated alkaline cleaner based on emulsifiers, surface-active agents and water.

Recommended use: For cleaning and degreasing of painted surfaces before recoating. Especially suited for removal of dirt, soot and uv light degraded surface-layers. Suited for use in high pressure cleaning equipment.

Availability: Subject to confirmation.

PHYSICAL CONSTANTS:

Colours/Shade nos:	Transparent/00000
Flash point:	Non flammable
Specific gravity:	1.0 kg/litre
pH value:	App.10 undiluted
V.O.C:	0 g/litre

The physical constants stated are nominal data according to the BLAKES Group's approved formulas. They are subject to normal manufacturing tolerances and where stated, being standard deviation according to ISO 3534-1. Further reference is made to "Explanatory Notes" in the BLAKES PAINT MANUAL.

Application method: Apply by stiff brush or by spraying using lowest possible pressure. To be diluted with fresh water: 1-50 parts of fresh water to 1 part of BLAKES SURFACE CLEANER. After 15 minutes the surface must be high pressure hosed with fresh water or carefully scrubbed with plenty of fresh water until all residues have been removed. If BLAKES SURFACE CLEANER leaves a white film, it can be removed with warm water. Can be used undiluted as cleaner for brushes.

Remarks: Shake BLAKES SURFACE CLEANER before use.
Due to alkaline properties BLAKES SURFACE CLEANER is not suited for cleaning of aluminium.
Do not expose to frost

Note: The information given in the Technical Data Sheet is intended for commercial use.

Safety: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult BLAKES PAINTS Material Safety Data Sheets and follow all local or national safety regulations. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment. Apply only in well ventilated areas.

Issued: JUNE 2004 - 6760100000CS001
BLAKES PAINTS

This Product Data Sheet supersedes those previously issued. For definition and scope, see explanatory notes to applicable Product Data Sheets.

Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User. The Products are supplied and all technical assistance is given subject to BLAKES PAINTS GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise.

Product data are subject to change without notice and become void five years from the date of issue.