

## BLAKES TEAK CLEANER

67543

<b>Description:</b>	BLAKES TEAK CLEANER is a cleaning powder for teak. Harmless to glass fibre, painted or varnished surfaces. Avoid contact with stainless steel.
<b>Recommended use:</b>	For cleaning of teak. Especially suited for large areas like decks.
<b>Availability:</b>	Subject to confirmation.
<b>PHYSICAL CONSTANTS:</b>	
Colours/Shade nos:	White/99980
Specific gravity:	1.0 kg/litre - 8.3 lbs/US gallon
	<small>The physical constants stated are nominal data according to the BLAKES Group's approved formulas. They are subject to normal manufacturing tolerances and where stated, being standard deviation according to ISO 3534-1. Further reference is made to "Explanatory Notes" in the BLAKES PAINT MANUAL.</small>
<b>Application conditions:</b>	Wet the surface with clean fresh water and apply a layer of BLAKES TEAK CLEANER. Distribute the powder in a uniform layer with brush. The surface must be wetted sufficiently to keep the powder moist. After approximately 10-15 minutes when the powder is still moist the surface is thoroughly brushed with a stiff brush. Clean the surface thoroughly with clean fresh water. Depending on the application conditions the treatment may be repeated.
<b>Subsequent coat:</b>	BLAKES TEAK COLOUR RESTORER (not for use on decks) and BLAKES TEAK OIL.
<b>Remarks:</b> Note:	Stainless steel parts must be protected against contact with BLAKES TEAK CLEANER. <b>The information given in the Product Data Sheet is intended for professional use.</b>
<b>Safety:</b>	Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult BLAKES PAINTS Material Safety Data Sheets and follow all local or national safety regulations. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment. Apply only in well ventilated areas.
<b>Issued:</b>	JUNE 2004 - 6754399980 BLAKES PAINTS

***This Product Data Sheet supersedes those previously issued. For definition and scope, see explanatory notes to applicable Product Data Sheets.***

***Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User. The Products are supplied and all technical assistance is given subject to BLAKES PAINTS GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise. Product data are subject to change without notice and become void five years from the date of issue.***

## BLAKES TEAK CLEANER

67543

<b>Description:</b>	BLAKES TEAK CLEANER is a cleaning powder for teak. Harmless to glass fibre, painted or varnished surfaces. Avoid contact with stainless steel.
<b>Recommended use:</b>	For cleaning of teak. Especially suited for large areas like decks.
<b>Availability:</b>	Subject to confirmation.
<b>PHYSICAL CONSTANTS:</b>	
Colours/Shade nos:	White/99980
Specific gravity:	1.0 kg/litre - 8.3 lbs/US gallon
	<small>The physical constants stated are nominal data according to the BLAKES Group's approved formulas. They are subject to normal manufacturing tolerances and where stated, being standard deviation according to ISO 3534-1. Further reference is made to "Explanatory Notes" in the BLAKES PAINT MANUAL.</small>
<b>Application conditions:</b>	Wet the surface with clean fresh water and apply a layer of BLAKES TEAK CLEANER. Distribute the powder in a uniform layer with brush. The surface must be wetted sufficiently to keep the powder moist. After approximately 10-15 minutes when the powder is still moist the surface is thoroughly brushed with a stiff brush. Clean the surface thoroughly with clean fresh water. Depending on the application conditions the treatment may be repeated.
<b>Subsequent coat:</b>	BLAKES TEAK COLOUR RESTORER (not for use on decks) and BLAKES TEAK OIL.
<b>Remarks:</b> Note:	Stainless steel parts must be protected against contact with BLAKES TEAK CLEANER. <b>The information given in the Product Data Sheet is intended for professional use.</b>
<b>Safety:</b>	Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult BLAKES PAINTS Material Safety Data Sheets and follow all local or national safety regulations. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment. Apply only in well ventilated areas.
<b>Issued:</b>	JUNE 2004 - 6754399980 BLAKES PAINTS

***This Product Data Sheet supersedes those previously issued. For definition and scope, see explanatory notes to applicable Product Data Sheets.***

***Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User. The Products are supplied and all technical assistance is given subject to BLAKES PAINTS GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise. Product data are subject to change without notice and become void five years from the date of issue.***