

# Product Data



## BLAKES TEAK OIL

67571

**Description:** BLAKES TEAK OIL is based on alkyd resin with natural oils which offers good penetration into the wood and high resistance to weather the marine environment. May be used to overcoat Teak Colour Restorer on areas of high useage. Contains anti fungal agents and brings out the natural colour of the wood. For use above the waterline.

**Recommended use:** On new teak and teak previously treated with oil based products, interior and exterior. Not suited for varnished surfaces.

**Availability:** Subject to confirmation.

### PHYSICAL CONSTANTS:

Colours/Shade nos:	Transparent/00000
Finish:	Transparent
Volume solids, %:	20 ± 1
Flash point:	38°C/100°F
Specific gravity:	0.8 kg/litre - 6.7 lbs/US gallon
Dry to touch:	8 hours at 20°C/68°F - depending on wood density 18 hours at 10°C/50°F - depending on wood density

*The physical constants stated are nominal data according to the BLAKES Group's approved formulas. They are subject to normal manufacturing tolerances and where stated, being standard deviation according to ISO 3534-1. Further reference is made to "Explanatory Notes" in the BLAKES PAINT MANUAL.*

### APPLICATION DETAILS:

Application method:	Brush	Dipping	Rag wiping
Thinner (max. vol.):	Do not dilute		
Cleaning of tools:	BLAKES THINNER No 1		
Indicated film thickness:	Not relevant (see REMARKS overleaf)		
Recoat interval, min:	When dry		

**Safety:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult BLAKES PAINTS Material Safety Data Sheets and follow all local or national safety regulations. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment. Apply only in well ventilated areas.

Issued:

JUNE 2004

## 2. BLAKES TEAK OIL

SURFACE PREPARATION:	<b>Untreated wood:</b> Remove any oil, grease etc. with BLAKES SURFACE CLEANER, hose down with clean fresh water. Clean the surface with BLAKES TEAK CLEANER. Rough surfaces may possibly be abraded with paper 180-220, remove dust. <b>Previously treated wood:</b> Remove any oil, grease, etc. with BLAKES SURFACE CLEANER. Hose down the surface with clean fresh water, allow to dry.
APPLICATION CONDITIONS:	The surface must be completely clean and dry. Apply only in dry weather and at temperatures above 5°C/41°F. In confined spaces provide adequate ventilation during application and drying.
SUBSEQUENT COAT:	None.
REMARKS:	Apply BLAKES TEAK OIL abundantly. Allow the wood to absorb the sealer for some minutes before any surplus is removed with clean rags to avoid a glossy film after drying. It is possible to abrade in the still wet sealer with paper 180-220, abrading parallel to grain. Spreading rate depends on the structure and absorption of the wood. Maintenance is carried out by BLAKES TEAK OIL, which is applied in a thin coat followed by removal of any surplus by clean rags. To avoid staining remove promptly any Teak Oil splashed onto gelcoat or paint coating. Beware that over application of BLAKES TEAK OIL could result in making the surface slippery, which could be dangerous on decks. <b>As auto ignition of rags impregnated with BLAKES TEAK OIL is possible, they should be safely disposed after use.</b>
Note:	<b>The information given in the Product Data Sheet is intended for professional use.</b>
ISSUED:	JUNE 2004 - 6757100000 BLAKES PAINTS

***This Product Data Sheet supersedes those previously issued. For definition and scope, see explanatory notes to applicable Product Data Sheets.***

***Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User. The Products are supplied and all technical assistance is given subject to BLAKES PAINTS GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise.***

***Product data are subject to change without notice and become void five years from the date of issue.***