

1 Identification of substance

- Product details
- Trade name: Epifanes Multi Marine Primer white
- Application of the substance / the preparation
Coating compound/ Surface coating/ paint
- Manufacturer/Supplier:
W.HEEREN & ZOON BV
Postbus 166
1430 AD Aalsmeer
- Information department: Environment protection department.

2 Composition/Data on components

- Chemical characterization
- Description:
Mixture of the substances listed below with nonhazardous additions.

• Dangerous components:

64742-48-9	Naphtha (petroleum), hydrotreated heavy Xn; R 10-65-66	25-50%
1330-20-7	xylene Xn; R 10-20/21-38	2.5-10%
546-93-0	Magnesite	2.5-10%
1314-13-2	zinc oxide N; R 50/53	≤ 2.5%

- Additional information:
For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- Hazard description: Not applicable.
- Information pertaining to particular dangers for man and environment:
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
R 10 Flammable.
R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 66 Repeated exposure may cause skin dryness or cracking.
- Classification system:
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.
- NFPA ratings (scale 0 - 4)
Health = 2
Fire = 2
Reactivity = 0
- HMIS-ratings (scale 0 - 4)
Health = 2
Fire = 2
Reactivity = 0

Printing date 01/14/2005

Reviewed on 01/14/2005

Trade name: Epifanes Multi Marine Primer white

(Contd. of page 1)

4 First aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

5 Fire fighting measures

- Suitable extinguishing agents:
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Protective equipment: No special measures required.

6 Accidental release measures

- Person-related safety precautions:
Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection:
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

7 Handling and storage

- Handling:
- Information for safe handling:
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about protection against explosions and fires:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

8 Exposure controls and personal protection

- Additional information about design of technical systems:
No further data; see item 7.

(Contd. on page 3)

Trade name: Epifanes Multi Marine Primer white

(Contd. of page 2)

- Components with limit values that require monitoring at the workplace:

1330-20-7 xylene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm (o-, m-, & p-isomers)
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

546-93-0 Magnesite

PEL	15*; 5** mg/m ³ *Total dust **Respirable fraction
REL	10*; 5** mg/m ³ *Total dust **Respirable fraction
TLV	10 mg/m ³ (e)

- Additional information:
The lists that were valid during the creation were used as basis.
- Personal protective equipment:
- General protective and hygienic measures:
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
- Breathing equipment:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Protection of hands:
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Tightly sealed goggles

9 Physical and chemical properties

- General Information

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic

(Contd. on page 4)

Trade name: Epifanes Multi Marine Primer white

(Contd. of page 3)

• Change in condition	Melting point/Melting range: Undetermined. Boiling point/Boiling range: 100°C (212°F)
• Flash point:	40°C (104°F)
• Ignition temperature:	240°C (464°F)
• Auto igniting:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
• Explosion limits:	Lower: 0.6 Vol % Upper: 7.0 Vol %
• Vapor pressure at 20°C (68°F):	1 hPa (1 mm Hg)
• Density at 20°C (68°F):	1.25 g/cm ³
• Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
• Viscosity:	Kinematic at 20°C (68°F): 35 s (ISO 6 mm)
• Solvent content:	Organic solvents: 36.0 % VOC content: 35.9 % VOC content:
• Solids content:	63.0 %

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Dangerous reactions No dangerous reactions known.
- Dangerous products of decomposition: No dangerous decomposition products known.

11 Toxicological information

- Acute toxicity:

• LD/LC50 values that are relevant for classification:		
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)
1330-20-7 xylene		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
1314-13-2 zinc oxide		
Oral	LD50	7950 mg/kg (mouse)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.

(Contd. on page 5)

Printing date 01/14/2005

Reviewed on 01/14/2005

Trade name: Epifanes Multi Marine Primer white

(Contd. of page 4)

- Sensitization: No sensitizing effects known.

12 Ecological information

- Ecotoxicological effects:
- Remark: Harmful to fish
- General notes:
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

13 Disposal considerations

- Product:
- Recommendation:
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- DOT regulations:
- Hazard class: 3
- Identification number: UN1263
- Packing group: III
- Proper shipping name (technical name): PAINT
- Label: 3
- Land transport ADR/RID (cross-border):
- ADR/RID class: 3 Flammable liquids
- Danger code (Kemler): 30
- UN-Number: 1263
- Packaging group: III
- Description of goods: 1263 PAINT
- Maritime transport IMDG:
- IMDG Class: 3
- UN Number: 1263
- Label: 3
- Packaging group: III
- EMS Number: F-E, S-E
- Marine pollutant: No
- Proper shipping name: PAINT
- Air transport ICAO-TI and IATA-DGR:
- ICAO/IATA Class: 3
- UN/ID Number: 1263
- Label: 3
- Packaging group: III
- Proper shipping name: PAINT

- USA -

(Contd. on page 6)

Trade name: Epifanes Multi Marine Primer white

(Contd. of page 5)

15 Regulations

• Sara

• Section 355 (extremely hazardous substances):

None of the ingredient is listed.

• Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
-----------	--------

• TSCA (Toxic Substances Control Act):

64742-48-9	Naphtha (petroleum), hydrotreated heavy
------------	---

13463-67-7	titanium dioxide
------------	------------------

1330-20-7	xylene
-----------	--------

16389-88-1	dolomite
------------	----------

14807-96-6	Talc (Mg3H2(SiO3)4)
------------	---------------------

546-93-0	Magnesite
----------	-----------

1314-13-2	zinc oxide
-----------	------------

68409-80-3	Isomeren van vetzure calciumzouten, C6-C19 Isomers from fatty acid salts
------------	---

68953-58-2	Ditallowdimethylammonium
------------	--------------------------

96-29-7	2-butanone oxime
---------	------------------

112-34-5	2-(2-butoxyethoxy)ethanol
----------	---------------------------

136-52-7	cobalt bis(2-ethylhexanoate)
----------	------------------------------

14808-60-7	Quartz (SiO2)
------------	---------------

• Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

• Cancerogenity categories

• EPA (Environmental Protection Agency)

1330-20-7	xylene	D
-----------	--------	---

1314-13-2	zinc oxide	D
-----------	------------	---

• IARC (International Agency for Research on Cancer)

13463-67-7	titanium dioxide	3
------------	------------------	---

1330-20-7	xylene	3
-----------	--------	---

14807-96-6	Talc (Mg3H2(SiO3)4)	3
------------	---------------------	---

136-52-7	cobalt bis(2-ethylhexanoate)	2B
----------	------------------------------	----

14808-60-7	Quartz (SiO2)	1
------------	---------------	---

• NTP (National Toxicology Program)

14808-60-7	Quartz (SiO2)	K
------------	---------------	---

• TLV (Threshold Limit Value established by ACGIH)

13463-67-7	titanium dioxide	A4
------------	------------------	----

1330-20-7	xylene	A4
-----------	--------	----

14807-96-6	Talc (Mg3H2(SiO3)4)	A4
------------	---------------------	----

14808-60-7	Quartz (SiO2)	A2
------------	---------------	----

• MAK (German Maximum Workplace Concentration)

96-29-7	2-butanone oxime	2
---------	------------------	---

(Contd. on page 7)

Trade name: Epifanes Multi Marine Primer white

(Contd. of page 6)

14808-60-7	Quartz (SiO ₂)	1
<ul style="list-style-type: none"> • NIOSH-Ca (National Institute for Occupational Safety and Health) 		
13463-67-7	titanium dioxide	
14808-60-7	Quartz (SiO ₂)	
<ul style="list-style-type: none"> • OSHA-Ca (Occupational Safety & Health Administration) 		
None of the ingredients is listed.		

- Product related hazard informations:
The product has been classified and marked in accordance with directives on hazardous materials.
- Risk phrases:
 - 10 Flammable.
 - 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 - 66 Repeated exposure may cause skin dryness or cracking.
- Safety phrases:
 - 2 Keep out of the reach of children.
 - 7 Keep container tightly closed.
 - 23 Do not breathe fumes/aerosol.
 - 24 Avoid contact with skin.
 - 46 If swallowed, seek medical advice immediately and show this container or label.
 - 51 Use only in well-ventilated areas.
- National regulations:
- Technical instructions (air):

Class	Share in %
I	≤ 2,5
NK	25-50

- Water hazard class:
Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing MSDS: Environment protection department.
- Contact: J.J. van Dijk