

Material Safety Data Sheet

According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 28.05.2003

1 Identification of the substance/preparation and of the company/undertaking

- Product details
- Trade name: Epifanes Multiguard
- Application of the substance / the preparation
Paint
Multifunctional tarfree alternative to traditional coaltar
- Manufacturer/Supplier:
W.HEEREN & ZOON BV
Postbus 166
1430 AD Aalsmeer
tel. +31-297-360366
fax. +31-297-342078
- Further information obtainable from: Department Research & Development
- Information in case of emergency: See under Manufacturer/Supplier

2 Composition/information on ingredients

- Chemical characterization
- Description:
Resin mixture
Solvent mixture with pigment additives

• Dangerous components:

CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Xn, N; R 10-37-51/53-65-66	12.909%
CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy Xn; R 10-65-66	34.15%

- Additional information:
For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- Hazard description: Not applicable.
- Information concerning particular hazards for human and environment:
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
R 10 Flammable.
R 66 Repeated exposure may cause skin dryness or cracking.
- Classification system:
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First-aid measures

- After inhalation:
Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page^{GE2})

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 28.05.2003

Trade name: Epifanes Multiguard

(Contd. of page 1)

5 Fire-fighting measures

- Suitable extinguishing agents:
CO₂, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents:
Water
Water with full jet
- Protective equipment: No special measures required.

6 Accidental release measures

- Person-related safety precautions: Ensure adequate ventilation
- Measures for environmental protection:
Do not allow product to reach sewage system or any water course.
Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- Handling:
- Information for safe handling: Work only in fume cupboard.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- Storage:
- Requirements to be met by storerooms and receptacles:
No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.

8 Exposure controls/personal protection

- Additional information about design of technical facilities:
No further data; see item 7.

- Ingredients with limit values that require monitoring at the workplace:
916 93 00 Magnesite

OES	Long-term value: 10* 4** mg/m ³ *total inhalable dust **respirable dust
-----	---------------------------------------------------------------------------------------

- Additional information:
The lists valid during the making were used as basis.
- Personal protective equipment:
- General protective and hygienic measures:
Wash hands before breaks and at the end of work.
- Respiratory protection: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/
the substance/ the preparation.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 28.05.2003

Trade name: Epifanes Multiguard

(Contd. of page 2)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Safety glasses

9 Physical and chemical properties

- General Information

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

- Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	niet bepaald °C

- Flash point: > 36°C

- Ignition temperature: 240°C

- Self-igniting: Product is not selfigniting.

- Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- Explosion limits:

Lower:	0.7 Vol %
Upper:	7.5 Vol %

- Vapour pressure at 20°C: 5 hPa

- Density at 20°C: 1.01 g/cm³

- Solubility in / Miscibility with water: Insoluble.

- Viscosity:

Kinematic at 20°C: 50 s (ISO 6 mm)

- Solvent content:

Organic solvents: 44.5 %

- Solids content: 55.5 % (VB% 1h 150C)

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- Dangerous reactions No dangerous reactions known.

(Contd. on page 4)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 28.05.2003

Trade name: Epifanes Multiguard

(Contd. of page 3)

- Dangerous decomposition products:
No dangerous decomposition products known.

11 Toxicological information

- Acute toxicity:

- LD/LC50 values relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6800 mg/kg (rat)

Dermal LD50 >3400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral LD50 >5000 mg/kg (rat)

Dermal LD50 >3000 mg/kg (rab)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.

12 Ecological information

- General notes:
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.

13 Disposal considerations

- Product:
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation:
Disposal must be made according to official regulations.

14 Transport information

- Land transport ADR/RID (cross-border)



- ADR/RID class: 3 F1 Flammable liquids.
- Danger code (Kemler): 30
- UN-Number: 1263
- Packaging group: III
- Hazard label: 3

(Contd. on page 5)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 28.05.2003

Trade name: Epifanes Multiguard

(Contd. of page 4)

- Description of goods: 1263 PAINT (not viscous)

- Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1263
- Label: 3
- Packaging group: III
- EMS Number: F-E,S-E
- Marine pollutant: No
- Proper shipping name: PAINT

- Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN/ID Number: 1263
- Label: 3
- Packaging group: III
- Proper shipping name: PAINT

15 Regulatory information

- Labelling according to EU guidelines:
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- Hazard-determining components of labelling:
Naphtha (petroleum), hydrodesulfurized heavy
Solvent naphtha (petroleum), light arom.
Naphtha (petroleum), hydrotreated heavy
- Risk phrases:
10 Flammable.
66 Repeated exposure may cause skin dryness or cracking.
- Safety phrases:
2 Keep out of the reach of children.
29 Do not empty into drains.
37 Wear suitable gloves.
46 If swallowed, seek medical advice immediately and show this container or label.
- National regulations:
- Technical instructions (air):

Class	Share in %
II	13.0
III	0.4

(Contd. on page 6)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 28.05.2003

Trade name: Epifanes Multiguard

(Contd. of page 5)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Relevant R-phrases

10 Flammable.

37 Irritating to respiratory system.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

• Department issuing MSDS: Department Research & Development

• Contact: T.J.H.M. van Steenes