

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 04.09.2002


1 Identification of the substance/preparation and of the company/ undertaking

- Product details
- Trade name: Epifanes Teak Oil Sealer
- Application of the substance / the preparation
Wood preservatives
Am impregnating oil for tropical woods
- Manufacturer/Supplier:
W.HEEREN & ZOON BV
Postbus 166
1430 AD Aalsmeer
tel. +31-297-360366
fax. +31-297-342078
- Further information obtainable from: Department Research & Development
- Information in case of emergency: See under Manufacturer/Supplier

2 Composition/information on ingredients

- Chemical characterization
- Description:
Resin mixture
Solvent mixture with additives

• Dangerous components:

CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	39.568%
EINECS: 265-150-3	 Xn; R 10-65-66	

- Additional information:
For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- Hazard description: Not applicable.
- Information concerning particular hazards for human and environment:
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
R 10 Flammable.
R 66 Repeated exposure may cause skin dryness or cracking.
- Classification system:
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First-aid measures

- After inhalation:
Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

- Suitable extinguishing agents:
CO₂, sand, extinguishing powder. Do not use water.

(Contd. on page 2)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 04.09.2002

Trade name: Epifanes Teak Oil Sealer

(Contd. of page 1)

- For safety reasons unsuitable extinguishing agents:
Water
Water with full jet
- Protective equipment: No special measures required.

6 Accidental release measures

- Person-related safety precautions: Ensure adequate ventilation
- Measures for environmental protection:
Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- Handling:
- Information for safe handling:
Ensure good ventilation/exhaustion at the workplace.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- Storage:
- Requirements to be met by storerooms and receptacles:
Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.

8 Exposure controls/personal protection

- Additional information about design of technical facilities:
No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information:
The lists valid during the making were used as basis.
- Personal protective equipment:
- General protective and hygienic measures:
Wash hands before breaks and at the end of work.
- Protection of hands:
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 04.09.2002

Trade name: Epifanes Teak Oil Sealer

(Contd. of page 2)

- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Safety glasses

9 Physical and chemical properties

• General Information

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

• Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	150°C

• Flash point: 42°C

• Ignition temperature: 240°C

• Self-igniting: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

• Explosion limits:

Lower:	0.6 Vol %
Upper:	7.0 Vol %

• Vapour pressure at 20°C: 1 hPa

• Density at 20°C: 0.88 g/cm³ (ISO 2811)

• Solubility in / Miscibility with water: Insoluble.

• Viscosity:

Kinematic at 20°C:	14 s (ISO 6 mm)
--------------------	-----------------

• Solvent content:

Organic solvents:	+ -1.5 42.7 %
-------------------	---------------

• Solids content:	+ -1.5 57.3 % (SC% 1h 150C)
-------------------	-----------------------------

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- Dangerous reactions No dangerous reactions known.
- Dangerous decomposition products:
No dangerous decomposition products known.

11 Toxicological information

• Acute toxicity:

• LD/LC50 values relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>3000 mg/kg (rab)
--------	------	-------------------

(Contd. on page 4)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 04.09.2002

Trade name: Epifanes Teak Oil Sealer

(Contd. of page 3)

- Primary irritant effect:
- on the skin: No irritant effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

12 Ecological information

- General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- Product:
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation:
Disposal must be made according to official regulations.

14 Transport information

- Land transport ADR/RID (cross-border)



- ADR/RID class: 3 F1 Flammable liquids.
- Danger code (Kemler): 30
- UN-Number: 1263
- Packaging group: III
- Hazard label 3
- Description of goods: 1263 PAINT RELATED MATERIAL

- Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1263
- Label 3
- Packaging group: III
- EMS Number: F-E,S-E
- Marine pollutant: No

(Contd. on page 5)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 19.03.2004

Reviewed on 04.09.2002

Trade name: Epifanes Teak Oil Sealer

(Contd. of page 4)

- Proper shipping name: PAINT
- Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN/ID Number: 1263
- Label: 3
- Packaging group: III
- Proper shipping name: PAINT

15 Regulatory information

- Labelling according to EU guidelines:
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- Hazard-determining components of labelling:
Naphtha (petroleum), hydrotreated heavy
- Risk phrases:
10 Flammable.
66 Repeated exposure may cause skin dryness or cracking.
- Safety phrases:
2 Keep out of the reach of children.
24 Avoid contact with skin.
43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
46 If swallowed, seek medical advice immediately and show this container or label.
51 Use only in well-ventilated areas.
- Special labelling of certain preparations:
Contains 2-butanone oxime. May produce an allergic reaction.
- National regulations:
- Technical instructions (air):

Class	Share in %
I	0.6
III	0.2
- Waterhazard class:
Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant R-phrases
10 Flammable.
65 Harmful: may cause lung damage if swallowed.
66 Repeated exposure may cause skin dryness or cracking.
- Department issuing MSDS: Department Research & Development
- Contact: T.J.H.M. van Steenes