

PRODUCT DESCRIPTION

Professional wipe down solvent designed to remove surface contaminants such as waxes, oils and sanding residues, prior to application of Perfection.

PRODUCT INFORMATION

Colour	ITA075-Clear
Specific Gravity	0.75
Typical Shelf Life	2 yrs
VOC (As Supplied)	750 g/lit
Unit Size	5 Lt , 200 Lt

DRYING/OVERCOATING INFORMATION

Drying

Overcoating Substrate Temperature

Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max
---------------	-----	-----	-----	-----	-----	-----	-----	-----

APPLICATION AND USE

- Preparation** Surface must be thoroughly cleaned before sanding. Remove dust by using a vacuum or dry compressed air while wiping surface with dry, clean cotton cloths.
- Method** Surface should be cleaned using the "Two Cloth Cleaning Method". Soak one cloth in 600 Wipedown Solvent and use this to wet the surface. Quickly wipe with a dry second cloth to remove the contaminants. The solvent must not be allowed to dry on the surface. Work small areas at a time, so that the second cloth wipes it clean and dry. Repeat until all residue is removed, changing cloths frequently.
- Hints** **Other** Using only one set of cloths or one wet cloth only smears contamination around. Any sanding residue left on the surface can impair the finish.
- Compatibility/Substrates** Do not use for cleaning substrates such as Aluminium. Do not use as a thinner or reducer

Recommended DFT

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

- Storage** TRANSPORTATION:
600 Wipedown Solvent should be kept in securely closed containers during transport and storage.
STORAGE:
Exposure to air and extremes of temperature should be avoided. For the full shelf life of 600 Wipedown Solvent to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/40°F and 35°C/95°F. Keep out of direct sunlight.
- Safety** DISPOSAL: Reminders of 600 Wipedown Solvent cannot be disposed of through the municipal waste route or dumped without permit. Disposal of reminders must be arranged for in consultation with the authorities.

IMPORTANT NOTES

written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal or injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

X and International are registered trademarks of Akzo Nobel.

Regional Addresses

Head Office

International Paint Ltd
P O Box 20980
Oriel House
16 Connaught Place
London W2 2ZB
United Kingdom
tel: +44 (0) 171 479 6000
fax: +44 (0) 171 479 6500

European Region

International Paint Ltd
Stoneygate Lane
Felling, Gateshead
Tyne & Wear NE10 0JY
United Kingdom
tel: +44 (0) 191 469 6111
fax: +44 (0) 191 438 3977

Asia Region

International Paint Singapore
(Pte) Ltd
449 Tagore Industrial Avenue
01-03 Hong Joo Industrial
Building
Singapore 787820
tel: +65 6453 1981
fax: +65 6453 1778

Australasia Region

International Paint
115 Hyde Road
Yeronga, Brisbane
Queensland 4104
Australia
tel: +61 (0) 7 3892 8866
fax: +61 (0) 7 3892 4287

North America Region

International Paint LLC
2270 Morris Avenue
Union
New Jersey 07083
USA
tel: +1 (0) 908 686 1300
fax: +1 (0) 908 686 8545

South America Region

International Paint
Rod Rap tavares, KM 18.5
Predio Administrativo 11
Butanta CEP 05577-300
Sao Paulo, Brazil
tel: +55 (0) 11 3789 2000
fax: +55 (0) 11 3789 2200



Ref: 05000560
Issue Date: 8-Sep-2005
Supersedes: