

PRODUCT DESCRIPTION

International produces a choice of antifoulings for the professional market meeting the requirements of a wide range of yacht designs, construction materials, operations and locations. Most ranges are supplied in a variety of colours such as off white, blue, red and black. Consult with your local Technical Representative for further information.

PRODUCT INFORMATION

Colour	YBA000-White, YBA001-Blue, YBA002-Red, YBA003-Black
Finish	Matt
Specific Gravity	2.0
Volume Solids	50%
Typical Shelf Life	2 yrs
Unit Size	5 Lt 20 Lt

DRYING/OVERCOATING INFORMATION

Drying

	5°C	15°C	23°C	35°C
Immersion	24hrs	18hrs	16hrs	12hrs
Touch Dry [ISO]	12hrs	4hrs	3hrs	2hrs

Note: Consult the technical datasheet for the specific antifouling chosen for precise information.

Overcoating Substrate Temperature

Overcoated By	5°C		15°C		23°C		35°C	
	Min	Max	Min	Max	Min	Max	Min	Max
International Antifouling	24hrs	ext	16hrs	ext	6hrs	ext	4hrs	ext

Note: Consult the technical datasheet for the specific antifouling chosen for precise information.

APPLICATION AND USE

Number of Coats	As specified
Coverage	(Theoretical) - 5.00 (m ² /lt)
Recommended DFT	100 microns dry
Recommended WFT	200 microns wet
Application Methods	Brush, Roller, Airless Spray, Bottom Feed Pressure Pot Spray

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	<p>GENERAL INFORMATION: Exposure to air and extremes of temperature should be avoided. For the full shelf life of International Antifouling to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/40°F and 35°C/95°F. Keep out of direct sunlight.</p> <p>TRANSPORTATION: International Antifouling should be kept in securely closed containers during transport and storage.</p>
Safety	<p>GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line.</p> <p>DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal.</p> <p>Remainders of International Antifouling cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.</p>

DISCLAIMER

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal or injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

X and International are registered trademarks of Akzo Nobel.

Regional Addresses

Head Office

International Coatings Ltd
P O Box 20980
Oriol House
16 Connaught Place
London W2 2ZB
United Kingdom
tel: +44 (0) 171 479 6000
fax: +44 (0) 171 479 6500

European Region

International Coatings Ltd
Stoneygate Lane
Felling, Gateshead
Tyne & Wear NE10 0JY
United Kingdom
tel: +44 (0) 191 469 6111
fax: +44 (0) 191 438 3977

Asia Region

International Coatings Pte Ltd
449 Tagore Industrial Avenue
01-03 Hong Joo Industrial
Building
Singapore 787820
tel: +65 6453 1981
fax: +65 6453 1778

Australasia Region

Akzo Nobel Pty Limited
115 Hyde Road
Yeronga, Brisbane
Queensland 4104
Australia
tel: +61 (0) 7 3892 8866
fax: +61 (0) 7 3892 4287

North America Region

International Paint Inc
2270 Morris Avenue
Union
New Jersey 07083
USA
tel: +1 (0) 908 686 1300
fax: +1 (0) 908 686 8545

South America Region

Akzo Nobel Coatings Ltd
Rod Rap tavares, KM 18.5
Predio Administrativo 11
Butanta CEP 05577-300
Sao Paulo, Brazil
tel: +55 (0) 11 3789 2000
fax: +55 (0) 11 3789 2200



Ref: 05000421
Issue Date: 14-Oct-2003
Supersedes: