

### PRODUCT DESCRIPTION

A liquid accelerator to accelerate the curing time and allow earlier tape time, which may be added to Interspray 900 (YZ series) and other 2-component polyurethanes.

### PRODUCT INFORMATION

<b>Colour</b>	YQA100
<b>Specific Gravity</b>	1.0
<b>Typical Shelf Life</b>	2 yrs
<b>Unit Size</b>	250 ml

### DRYING/OVERCOATING INFORMATION

#### Drying

#### Overcoating Substrate Temperature

Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max
---------------	-----	-----	-----	-----	-----	-----	-----	-----

### APPLICATION AND USE

<b>Preparation</b>	See datasheet for the product you wish to accelerate.
<b>Method</b>	The use of accelerator in Interspray 900 is fully described in the Professional Application Manual and recommended levels should not be exceeded otherwise reduced performance may result.
<b>Hints</b>	<p><b>Mixing</b> Mix the base and curing agents of Interspray 900 together at the specified mix ratio. Thin as required (see Interspray 900 datasheet for details). Stir thoroughly. Allow to stand for 5 minutes to allow entrapped air and gases to escape. Add Interspray Accelerator as per levels recommended below. Stir thoroughly. The paint is now ready for use. Addition levels per unit of Interspray 900 are as follows: 10°C/50°F-15°C/59°F: 10-25 ml . 15°C/59°F-20°C/70°F: 5-10 ml . 20°C/70°F-25°C/77°F: 0-10 ml . 25°C/77°F-30°C/86°F: 0-5 ml . &gt; 30°C/86°F: No addition required .</p> <p><b>Other</b> The new Interspray 900 (YZ series) has been formulated to give the ultimate finish under a wide range of conditions. To allow the product to perform in hot, tropical conditions, its natural curing rate has been adjusted for these conditions. Consequently, under more "normal" conditions the use of Interspray Accelerator may be necessary unless longer drying times are not a problem. The ultimate finish is obtained by the slowest cure of the product that you can accept.</p>
<b>Some Important Points</b>	Addition of excess accelerator can compromise the flow of the finish. Only to be applied in temperatures between 10°C/50°F-30°C/86°F.
<b>Compatibility/Substrates</b>	No special restrictions.

### Recommended DFT

### TRANSPORTATION, STORAGE AND SAFETY INFORMATION

<b>Storage</b>	<b>GENERAL INFORMATION:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of Interspray
----------------	---

Accelerator to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/40°F and 35°C/95°F. Keep out of direct sunlight.

**TRANSPORTATION:**

Interspray Accelerator should be kept in securely closed containers during transport and storage.

**Safety**

GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line.

DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal.

Remainders of Interspray Accelerator cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

**IMPORTANT NOTES**

*The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal or injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.*

**X** and International are registered trademarks of Akzo Nobel.

**Regional Addresses**

Head Office

International Paint Ltd  
P O Box 20980  
Oriol House  
16 Connaught Place  
London W2 2ZB  
United Kingdom  
tel: +44 (0) 171 479 6000  
fax: +44 (0) 171 479 6500

European Region

International Paint Ltd  
Stoneygate Lane  
Felling, Gateshead  
Tyne & Wear NE10 0JY  
United Kingdom  
tel: +44 (0) 191 469 6111  
fax: +44 (0) 191 438 3977

Asia Region

International Paint Singapore  
(Pte) Ltd  
449 Tagore Industrial Avenue  
01-03 Hong Joo Industrial  
Building  
Singapore 787820  
tel: +65 6453 1981  
fax: +65 6453 1778

Australasia Region

International Paint  
115 Hyde Road  
Yeronga, Brisbane  
Queensland 4104  
Australia  
tel: +61 (0) 7 3892 8866  
fax: +61 (0) 7 3892 4287

North America Region

International Paint Inc  
2270 Morris Avenue  
Union  
New Jersey 07083  
USA  
tel: +1 (0) 908 686 1300  
fax: +1 (0) 908 686 8545

South America Region

International Paint  
Rod Rap tavares, KM 18.5  
Predio Administrativo 11  
Butanta CEP 05577-300  
Sao Paulo, Brazil  
tel: +55 (0) 11 3789 2000  
fax: +55 (0) 11 3789 2200



Ref: 05000130  
Issue Date: 26-Sep-2004  
Supersedes: 4-Sep-2004