

## PRODUCT DESCRIPTION

Teak Oil is a special penetrating oil for protection of teak decks and teak interiors. It produces a protective and easy-clean surface.

- \* Penetrating wood treatment containing linseed and tung oils.
- \* Award-winning in comparative tests.
- \* For use on any interior or exterior hardwood.
- \* Produces attractive sheen finish.
- \* Penetrates even moist wood.
- \* Contains an anti-rust wax for metal surfaces.

## PRODUCT INFORMATION

<b>Colour</b>	YMA645-Yellow-brown
<b>Specific Gravity</b>	0.8
<b>Unit Size</b>	500 ml 5 Lt

## DRYING/OVERCOATING INFORMATION

### Drying

### Overcoating Substrate Temperature

Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max
---------------	-----	-----	-----	-----	-----	-----	-----	-----

## APPLICATION AND USE

<b>Preparation</b>	Ensure bare wood is clean and dry. Clean wood with Teak Restorer if required. If protection against rot is required, treat the surface with Intertox.
<b>Method</b>	Apply 1-2 coats of Teak Oil with a cloth or brush. Let the oil dry before touching. Repeat during the season if required.
<b>Hints</b>	<b>Mixing</b> Shake well before use.
<b>Some Important Points</b>	Product temperature should be minimum 5°C/40°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/40°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/40°F and maximum 35°C/95°F.
<b>Compatibility/Substrates</b>	Suitable for use on interior or exterior hardwood. Not sensitive to frost.
<b>Recommended DFT</b>	
<b>Application Methods</b>	Brush , cloth

## TRANSPORTATION, STORAGE AND SAFETY INFORMATION

<b>Storage</b>	<p><b>GENERAL INFORMATION:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of Teak Oil to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/40°F and 35°C/95°F. Keep out of direct sunlight.</p> <p><b>TRANSPORTATION:</b> Teak Oil should be kept in securely closed containers during transport and storage.</p>
----------------	---

## Safety

**GENERAL:** Read the label safety section for Health and Safety Information, also available from our Technical Help Line.  
**DISPOSAL:** Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal.  
Remainders of Teak Oil cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

## IMPORTANT NOTES

*The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal or injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.*

**X** and International are registered trademarks of Akzo Nobel.

## Regional Addresses

**Head Office**  
International Paint Ltd  
P O Box 20980  
Oriol House  
16 Connaught Place  
London W2 2ZB  
United Kingdom  
tel: +44 (0) 171 479 6000  
fax: +44 (0) 171 479 6500

**European Region**  
International Paint Ltd  
Stoneygate Lane  
Felling, Gateshead  
Tyne & Wear NE10 0JY  
United Kingdom  
tel: +44 (0) 191 469 6111  
fax: +44 (0) 191 438 3977

**Asia Region**  
International Paint Singapore  
(Pte) Ltd  
449 Tagore Industrial Avenue  
01-03 Hong Joo Industrial  
Building  
Singapore 787820  
tel: +65 6453 1981  
fax: +65 6453 1778

**Australasia Region**  
International Paint  
115 Hyde Road  
Yeronga, Brisbane  
Queensland 4104  
Australia  
tel: +61 (0) 7 3892 8866  
fax: +61 (0) 7 3892 4287

**North America Region**  
International Paint Inc  
2270 Morris Avenue  
Union  
New Jersey 07083  
USA  
tel: +1 (0) 908 686 1300  
fax: +1 (0) 908 686 8545

**South America Region**  
International Paint  
Rod Rap tavares, KM 18.5  
Predio Administrativo 11  
Butanta CEP 05577-300  
Sao Paulo, Brazil  
tel: +55 (0) 11 3789 2000  
fax: +55 (0) 11 3789 2200



Ref: 05000149  
Issue Date: 4-Sep-2004  
Supersedes: 13-Feb-2003