

Codice: 6A5073

Ecowood Finish Gloss

Water-based gloss topcoat for wood



Clear gloss water based gloss finish for wood. Formulated with UV filters to provide excellent weather resistance. Gives waterproofing characteristics, it is non-yellowing and has a good mildew resistance. The application of min.2 coats is recommended.

Technical Characteristics

Paint Type	One component solvent
Binder type A	Polyurethane acrylic
Specific gravity kg/lt (±0,05)	1.050
Solids content (weight) ±2	45%
Viscosity Ford ø 8 at 20°C ±2	120-10
Shelf life (+10+30°C)	18 months in airtight cans
Note	Keep in a cool, dry place, protect from frost

Application Data

Application	Brush-Roller-Spray
Brush-Roller	Ready for use or with 5% water
Spray	Ready for use or with 5% water
Touch dry	4-6 h
Recoat time	Min. 12 h
Application temperature	Between +10 C et +40 C
Relevant humidity	Less than 80%
Dry film thickness advised	30 dry microns
Theoret. coverage m2/Lt	11-12

SURFACE PREPARATION AND APPLICATION


Bare wood.

The substrate to be coated should be dry, clean and well seasoned. Apply 1 coat of water-based basecoat or ECOWOOD diluted. Let dry for 12-24 hours and overcoat with 2 coats of ECOWOOD FINISH GLOSS allowing 12 hours drying between coats (at room temperature).

Painted wood.

If the old paint is in sound conditions and it only needs to be renewed, clean and sandpaper the surface and apply 2 coats of ECOWOOD FINISH GLOSS allowing 12 hours between coats (at room temperature).

Colors



Colore: Lucido
Cod. Colore: 6A5073

Codice: 6A5073

Ecwood Finish Gloss



AEMME COLORI SRL, Via Patta 12, 24020 Ranica (BG), Italy
Tel: 035.513373 - Fax: 035.513211 - Mail: info@aemmecolori.it
R.E.A Bergamo 205139 - Reg. Imprese BG 21543 - P.IVA 00999580160

