

Epifanes Teak Oil Sealer

An impregnating oil for the maintenance and protection of teak and other oily and/or resinous types of wood. Accents the natural grain colour and protects the wood from discolouration caused by weather or pollutants. Ideal for use on teak decks.

Easy to apply by wide brush or lint-free cloth

Type	Oxidative drying
Base	Linseed oil / Alkyd resin
Colour	Amber
Gloss	n.a.
Density	0.91 kg/dm ³
Viscosity	20 seconds Din Cup 4 mm.
Solids Content	50 ± 2 vol.%
Surface preparation	Remove all dirt and spots with a non-sanding and non-bleaching detergent. Thoroughly degrease oily types of wood with Epifanes Spraythinner for Paint & Varnish or another suitable degreaser
Application	Apply wet-on-wet until saturation of the wood has been achieved. Saturation depends on the absorption power of the wood. In general two treatments are sufficient. Any film build-up must be avoided at all times. Remove surplus material with a lint-free cloth. Apply by wide brush or lint-free cloth.
Thinner	Epifanes Brushthinner for Paint & Varnish.
Maintenance interval	Dependant on atmospheric conditions.
Theoretical coverage	10 m ² per litre
Practical coverage	Dependant on absorption power of the wood, methode of application. Loss of material due the shape of object and circumstances during application.
Recommended use	All wooden areas where for risks of slipping the application of a smooth varnish or oil finish is not suitable or desired (i.e. decks, gangways, etc.). Can also be used for treatment of handles, railings and other areas of exotic wood where the natural appearance of the wood is preferred and should be maintained.
Safety information	Linseed oil is an oxidative drying oil type. During this process heat is developed. To avoid any risks of spontaneous auto-ignition it is advised to keep soaked rags and cloths in a well ventilated place or in a (closed) can filled with water . Remnants and rags should be disposed off in accordance with national and local regulations.