

Features & Uses

Tack rags are used just before painting to remove the lightest dust or dirt from what would otherwise be considered a clean, ready to paint surface.

Specification Data

Type: Premium Tack Rags
Packaging: 36 Packs of 4 equals 144 per case

Product Components, Reducers, Additives, and Auxiliary Components

Deluxe Tack Rags 73009

Application Equipment

N/A

Surface Preparation

Tack rags are used before final primer and topcoat applications. They are usually not needed when applying fairing materials or surfacers.

Mixing & Reduction

N/A

Application Instructions

When tacking a primer or topcoat surface, use only AWLGRIP® Deluxe Tack Rags (#73009). They have the proper type and amount of resin to pick up dust without leaving contamination on the surface. Other tack rags can easily leave a residue that causes fisheyes and cratering of the topcoat.

Be careful not to use excessive hand pressure when using tack rags. A light dusting is all that is necessary, let the resin do the work. Even AWLGRIP® Deluxe Tack Rags can leave a resin on the surface if used improperly.

The information in this Product Data Sheet is not intended to be exhaustive. Any person using the product without first making further enquiries as to the suitability of the product for the intended purpose does so at their own risk and, to the extent permitted by law, we can accept no responsibility for the performance of the product or for any loss or damage arising out of such use. The information contained in this Product Data Sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Awlgrip® and all products mentioned in this Product Data Sheet are trademarks of, or licensed to, Akzo Nobel.

© Akzo Nobel, 2005

1 East Water Street • Waukegan, Illinois 60085 • USA • Tel: 847.599.6212 • Fax: 847.599.6209
Bannerlaan 54 • B-2280 Grobbendonk • Belgium • Intl. Tel: 32.14.257770 • Intl. Fax: 32.14.230880
76 Waterway Drive • Coomera • QLD 4209 • Australia • Tel: 61.7.5573.9600 or 1800.007.866 • Fax: 61.7.5573.9677
449 Tagore Industrial Avenue • 01-03 Hong Joo Industrial Building • Singapore 787820 • Tel: 65.6453.1981 • Fax: 65.6453.1778