



SAFETY DATA SHEET

1. Identification of the preparation and of the company/undertaking

Product Name and/or Code	: SEATECH PRIMER 18508	
Company name and address	: Blakes Paints Swanwick Marina Southampton Hampshire SO31 7EF Telephone: 01489 864440	Emergency phone: 01489 864440 See section 4 First aid measures.
Product Type	: water borne epoxy primer (base for 2-component product)	
Field of application	: metal industry, private (yachts), ships and shipyards.	
Ready for use mixture	: 18508 6 LI / 97701 4 LI	
Date of issue	: 25-02-2004.	
Date of previous issue	: No Previous Validation.	

2. Composition/information on ingredients

Substances presenting a health hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

To present knowledge of the supplier, this product does not contain any hazardous ingredients in accordance to EU regulations or National regulations.

3. Hazards identification

Contains (3-aminomethyl-3,5,5- trimethylcyclohexylamine, bis-aminomethylbenzene, (benzothiazol-2-ylthio)succinic acid). May produce an allergic reaction.

4. First-aid measures

General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	: Move the person into fresh air and keep the person under surveillance.
Eye Contact	: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. In all cases of doubt, or when symptoms persist, seek medical attention.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting unless directed to do so by medical personnel. Lower the head so that the vomit will not reenter the mouth and throat.
Notes to physician	: If gasses have been inhaled, from the decomposition of the product, symptoms may be delayed.

5. Fire-fighting measures

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Fire-fighters should wear proper protective equipment. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

Extinguishing Media	: Recommended: alcohol resistant foam, CO ₂ , powders, water spray. Not to be used : waterjet.
Fire Degradation Products	: These products are nitrogen oxides (NO, NO ₂ ...), sulphur oxides (SO ₂ , SO ₃ , etc.). Some metallic oxides.

6. Accidental release measures

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth, and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulation

7. Handling and storage

Handling

Appropriate personal protective equipment: see Section 8.

Always keep in containers made from the same material as the original one.

Storage

Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

Storage : Do not store below 5 °C

8. Exposure controls/personal protection

- Engineering measures : Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.
- Hygiene measures : Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.
- Occupational Exposure Limits : Not applicable.

Personal protective equipment

- General : Gloves must be worn for all work that may result in soiling.
Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product.
- Skin and body : If necessary wear protective clothing. Always wear protective clothing when spraying.
- Hands : Wear suitable gloves. Barrier creams may help to protect the exposed areas of the skin, but should not be applied once exposure has occurred. Barrier creams may not be used under or instead of gloves.
It is not possible to specify precise type of gloves, since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type.
- Eyes : Use safety eyewear designed to protect against splash of liquids.
-

9. Physical and chemical properties

- Physical state : Liquid.
- Density : 1.448 g/cm³
- Solubility : Easily soluble in cold water, hot water.
- % by Weight : Weighted average: 0 %
- % by Weight : Weighted average: 46 %
- VOC Content : Weighted average: 1 g/l (CEPE)
- TOC Content : Weighted average: 1 g/l
- Solvent Gas : 0 m³/l paint

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Reactive with metals.

Slightly reactive to reactive with oxidising agents, acids.

When exposed to high temperatures (i.e. in case of fire) hazardous decomposition products may be formed:

These products are nitrogen oxides (NO, NO₂...), sulphur oxides (SO₂, SO₃, etc.). Some metallic oxides.

11. Toxicological information

Effects and symptoms

Sensitization : Contains (3-aminomethyl-3,5,5- trimethylcyclohexylamine, bis-aminomethylbenzene, (benzothiazol-2-ylthio)succinic acid). May produce an allergic reaction.

12. Ecological information

The product must not be drained into water courses or drainage system.

13. Disposal considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

European waste catalogue no. (EWC) and national waste group, catalogue, code or number is given below.

EWC no. : 08 01 12

14. Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea.

The transport classification is according to ADR 2003, IMDG edition 2002 (incl. Amdt. 31-02).

	UN-no.	Proper shipping name	Class	Packing group	Label	Additional Information
ADR/RID Class	Not dangerous goods		-	-		-
IMDG Class	Not dangerous goods		-	-		-

15. Regulatory information

Classification and labelling according to EU-Directives (the Preparations directive etc.).

Risk Phrases : This product is not classified according to the EU regulations.

Safety Phrases : S23- Do not breathe vapor/spray.

Additional Warning Phrases : Contains (3-aminomethyl-3,5,5- trimethylcyclohexylamine, bis-aminomethylbenzene, (benzothiazol-2-ylthio)succinic acid). May produce an allergic reaction.

Other EU regulations

Classification and labelling have been performed according to EU directives 67/548/EEC, 1999/45/EC, including amendments and the intended use.

- Industrial applications, Used by Spraying.

16. Additional Information

Full text of R phrases referred to in Sections 2 and 3 - United Kingdom (UK) :

Full text of classifications referred to in Sections 2 and 3 - United Kingdom (UK) :

Notice to Reader

Modified data or content compared with the previous version are marked with a triangular marker in the upper-left corner within the Safety Data Sheet.

The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical performance or suitability for particular applications. It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.