

**PRODUCT DESCRIPTION****PRODUCT INFORMATION**

Volume Solids	60%
Typical Shelf Life	2 yrs
VOC (As Supplied)	357 g/lt

**DRYING/OVERCOATING INFORMATION****Drying****Overcoating  
Substrate Temperature**

Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max
---------------	-----	-----	-----	-----	-----	-----	-----	-----

**APPLICATION AND USE**

**Coverage** (Theoretical) - 4.80 (m<sup>2</sup>/lt) @ 125 microns DFT

**Recommended DFT** 125 microns dry

**Recommended WFT** 208 microns wet

**TRANSPORTATION, STORAGE AND SAFETY INFORMATION****Storage****IMPORTANT NOTES**

 and International are registered trademarks of Akzo Nobel.

**Regional Addresses**

**Head Office**  
International Paint Ltd  
P O Box 20980  
Oriol House  
16 Connaught Place  
London W2 2ZB  
United Kingdom  
tel: +44 (0) 171 479 6000  
fax: +44 (0) 171 479 6500

**European Region**  
International Paint Ltd  
Stoneygate Lane  
Felling, Gateshead  
Tyne & Wear NE10 0JY  
United Kingdom  
tel: +44 (0) 191 469 6111  
fax: +44 (0) 191 438 3977

**Asia Region**  
International Paint Singapore  
(Pte) Ltd  
449 Tagore Industrial Avenue  
01-03 Hong Joo Industrial  
Building  
Singapore 787820  
tel: +65 6453 1981  
fax: +65 6453 1778

**Australasia Region**  
International Paint  
115 Hyde Road  
Yeronga, Brisbane  
Queensland 4104  
Australia  
tel: +61 (0) 7 3892 8866  
fax: +61 (0) 7 3892 4287

**North America Region**  
International Paint Inc  
2270 Morris Avenue  
Union  
New Jersey 07083  
USA  
tel: +1 (0) 908 686 1300  
fax: +1 (0) 908 686 8545

**South America Region**  
International Paint  
Rod Rap tavares, KM 18.5  
Predio Administrativo 11  
Butanta CEP 05577-300  
Sao Paulo, Brazil  
tel: +55 (0) 11 3789 2000  
fax: +55 (0) 11 3789 2200