

## PRODUCT DESCRIPTION

Effective rubbing paste for restoring deep gloss to GRP, painted surfaces and oxidised metal. It has been specifically developed to give a smooth, deep gloss finish to weathered gelcoat and painted surfaces. Minor scratches, stubborn stains and inground dirt may be removed with Yacht Rubbing. It is also recommended for polishing chrome and various oxidised metals such as aluminium, brass and stainless steel. For machine or manual use.

## PRODUCT INFORMATION

Colour	YMA630-White
Specific Gravity	1.3
Unit Size	500 ml

## DRYING/OVERCOATING INFORMATION

### Drying

### Overcoating Substrate Temperature

Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max
---------------	-----	-----	-----	-----	-----	-----	-----	-----

## APPLICATION AND USE

<b>Preparation</b>	Clean with Yacht Line Super Cleaner. Rinse with fresh water and allow to dry.
<b>Method</b>	Apply Yacht Rubbing with a clean, dry cloth. Polish with circular movements. Machine polishing (800-1000 rpm) is the most effective method. Polish the surface further with a dry, clean cloth. Protect the surface with Marine Polish and/or Marine Wax.
<b>Hints</b>	<b>Other</b> For a smoother effect, apply to a wet surface.
<b>Some Important Points</b>	Avoid working in direct sunlight. Sensitive to frost. Product temperature should be minimum 5°C/40°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/40°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/40°F and maximum 35°C/95°F.
<b>Compatibility/Substrates</b>	Suitable for use on GRP, painted and metal surfaces.
<b>Recommended DFT</b>	
<b>Application Methods</b>	Soft cloth or buffing machine.

## TRANSPORTATION, STORAGE AND SAFETY INFORMATION

<b>Storage</b>	<p><b>GENERAL INFORMATION:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of Yacht Rubbing to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/40°F and 35°C/95°F. Keep out of direct sunlight.</p> <p><b>TRANSPORTATION:</b> Yacht Rubbing should be kept in securely closed containers during transport and storage.</p>
<b>Safety</b>	<p><b>GENERAL:</b> Read the label safety section for Health and Safety Information, also available from our Technical Help Line.</p> <p><b>DISPOSAL:</b> Do not discard tins or pour paint into water courses, use the facilities provided. It is best</p>

to allow paints to harden before disposal.  
Remainders of Yacht Rubbing cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

## IMPORTANT NOTES

*The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal or injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.*

**X** and International are registered trademarks of Akzo Nobel.

## Regional Addresses

Head Office  
International Paint Ltd  
P O Box 20980  
Oriol House  
16 Connaught Place  
London W2 2ZB  
United Kingdom  
tel: +44 (0) 171 479 6000  
fax: +44 (0) 171 479 6500

European Region  
International Paint Ltd  
Stoneygate Lane  
Felling, Gateshead  
Tyne & Wear NE10 0JY  
United Kingdom  
tel: +44 (0) 191 469 6111  
fax: +44 (0) 191 438 3977

Asia Region  
International Paint Singapore  
(Pte) Ltd  
449 Tagore Industrial Avenue  
01-03 Hong Joo Industrial  
Building  
Singapore 787820  
tel: +65 6453 1981  
fax: +65 6453 1778

Australasia Region  
International Paint  
115 Hyde Road  
Yeronga, Brisbane  
Queensland 4104  
Australia  
tel: +61 (0) 7 3892 8866  
fax: +61 (0) 7 3892 4287

North America Region  
International Paint Inc  
2270 Morris Avenue  
Union  
New Jersey 07083  
USA  
tel: +1 (0) 908 686 1300  
fax: +1 (0) 908 686 8545

South America Region  
International Paint  
Rod Rap tavares, KM 18.5  
Predio Administrativo 11  
Butanta CEP 05577-300  
Sao Paulo, Brazil  
tel: +55 (0) 11 3789 2000  
fax: +55 (0) 11 3789 2200



Ref: 05000343  
Issue Date: 26-Sep-2004  
Supersedes: 4-Sep-2004