



SOLVENT / DEGREASER

S D

**FOR THE PREPARATION OF GRP SURFACES
TO BE PAINTED AND TO REMOVE WAX TRACKS**

DESCRIPTION

Nautix SD is especially recommended for the preparation of surfaces to be painted, mainly GRP new hulls, to eliminate wax and unmoulding tracks.

S.D. is a powerful solvent recommended for cleaning the tools used for resin application.

This product is way less volatile and flammable than acetone. Do not use this product on hatch cover and porthole.

COMPOSITION

Xylene, methylethylcetone, butanone.

WORKERS PROTECTION

Work in a well ventilated area, wear suitable protective clothing, gloves and eye/face protection.

PREPARATION - APPLICATION

Wash the surface with fresh water and detergent added, rinsed, and apply NAUTIX SD with a clean non fluffy cloth. Let the product drying through evaporation before painting.

TECHNICAL DATA

Pack sizes : 0,5 Ltr and 3Ltr.

Flash point : - 4°C.

Self-ignition : 460°C

SAFETY DATA

R 11 Highly flammable.
R 36 Irritating to eyes.
R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 65 Harmful. May cause lung damage if swallowed.
R 66 Repeated exposure may cause skin dryness or cracking.
R 67 Vapours may cause drowsiness and dizziness.

S 2 Keep out of reach of children.

S 46 If swallowed, seek medical advice immediately and show this container or label.

Emergency phone number : +33 (0)1 45 42 59 59

NAUTIX SA
Z.I. des 5 Chemins
56520 GUIDEL
FRANCE
Fax : + 33 (0)2 97 65 03 54
Tel : + 33 (0)2 97 65 32 69
E.mail : info@nautix.com
www.nautix.com