

RYLARD

www.RylardBoats.com

ANCILLARY PRODUCTS

Cement Filler White(A799)

Cement filler is supplied in paste form in white. It should always be applied after coats of primer and will flat down with wet or dry paper 3-4 hours after application. Whilst remaining flexible when dry it will not shrink or crack and is ideal for filling screw or nail holes, bruises or seams. When thinned with White Spirits large areas may be covered by 'broad knife' technique.

Slip Resistant Kit(40003)

Smooth fine aggregate powder designed for addition to Rylard Plus Enamel to produce a non-slip coating suitable for upper deck areas and walkways.

Supplied in a 1 litre size container, to produce an anti-slip paint simply add 1 x 750ml can of Rylard Plus Enamel of the chosen colour to the container and thoroughly stir. It is recommended that the anti-slip paint thus produced be applied by brush.

Terebine Driers(V59)

At certain times of the year, when the weather conditions are not ideal for painting(typically cold, damp conditions) the drying of Rylard products can be retarded. In these conditions it is acceptable to add additional paint driers to help alleviate the problem

Terebine Driers are a ready mixed drier combination that will assist the drying of Rylard products in poor weather conditions. Tests(under laboratory conditions) have shown that an addition of the driers will speed up the touch dry time by approximately 45 minutes.

Used by adding 5 capfuls of the supply container per 750ml can of Rylard undercoat, plus enamel or varnish. Stir thoroughly before use and where possible allow 6-8 hours standing after mixing before painting to allow the drier solution to be fully absorbed.

Distributed by:

Mainline
2 Sefton Road
Litherland
Liverpool L21 7PG
Tel: 0151 920 6451
Fax: 0151 920 6452

Your Local Stockist: