



[www.RylardBoats.com](http://www.RylardBoats.com)

# Technical Data Sheet

**PRODUCT NAME:** **COFLEX VT**

---

**CODE NUMBER:** 40029

---

**PRODUCT DESCRIPTION:** Vinyl Tar coating with excellent oil & diesel resistance, allied to abrasion resistance, flexibility and weather resistance. Coflex VT dries to a pleasant matt finish and exhibits good application properties

---

**PERFORMANCE/USE:** Can be used on ferrous, non-ferrous and masonry substrates. Gives protection against moisture ingress, both fresh and saline. Not affected by most oils and a range of chemicals. Although specifically formulated for narrow boats, can also be used for marine construction piles and chemical plants

---

**SURFACE PREPARATION:** **New Work:** Degrease and if possible shot blast to SA. 2<sup>1</sup>/<sub>2</sub>. Alternatively, mechanically abrade.  
**Refurbishment:** Pressure clean; de-rust as required and patch treat before full application.

---

**APPLICATION:** For Professional Use Only.  
Apply by brush; roller or airless spray. Use as supplied; thin if required with Coflex thinner  
Apply 3 coats on new work; 1-2 coats on refurbishment  
Minimum application temperature: 10°C

---

**DRYING/OVERCOATING:**

Drying time(10°C)	2-4 hours
Overcoating time(10°C)	2-4 hours
Launch time(10°C)	48 hours

---

**PHYSICAL PROPERTIES:**

Mixing Ratio	Single pack product
Thinner/Cleaner	Coflex thinner
Supply Viscosity	10 poise
Supply SG	1.25
Colour	Black
Gloss Level	Matt
Theoretical Coverage:	3.5 square metres per litre
VOC Content:	500 grammes per litre
Flash Point / Class / UN No	≥0°C & ≤21°C / II / UN 1999
Pack Size	5 & 20 litre containers
Shelf Life	12 months unopened, stored at UK ambient temperatures.
Health & safety:	Refer to Product Safety Data Sheet before use.

***This information is given in good faith for the guidance of users, but is without warranty or liability. Any queries should be referred to our technical department,***

**Distributed by:**  
**Mainline**  
2 Sefton Road  
Litherland  
Liverpool L21 7PG  
Tel: 0151 920 6451  
Fax: 0151 920 6452

**Your Local Stockist:**