



[www.RylardBoats.com](http://www.RylardBoats.com)

# Technical Data Sheet

**PRODUCT NAME:** ENGINE BAY PAINT - LIGHT GREY

**PRODUCT DESCRIPTION:** Traditional high quality long oil alkyd enamel formulated specifically as a gloss finish for engine bays and other below deck areas, to give excellent gloss and flow. Will give heat resistance up to 150°C.

**PERFORMANCE/USE:** Suitable for use as the finishing coat for engine bays and all below deck areas on all types of leisure marine craft, including narrowboats, river cruisers and yachts. Has excellent resistance to oils and fuels.  
Rylard Engine Bay Paint dries dust free in 3-4 hours and will be hard dry overnight. Excellent heat resistance makes Rylard Engine Bay Paint also ideal for use as an engine paint.

**SURFACE PREPARATION:** Always apply over fully prepared surfaces, the final undercoat being flatted with 320/360 wet & dry paper. Refer to our painting hints booklet before starting work.

**APPLICATION:** Apply by brush; roller; paint pad or spray. Use as supplied; thin if required with Ry-thin thinner; recommended addition 5-10% depending upon spray equipment.  
Minimum application temperature: 10°C

**DRYING/OVERCOATING:**

Touch/Dust Dry(15°C)	4 hours
Hard dry/Overcoating(15°C)	16-24 hours

**COLOURS/CODES:** Code Number: 32014; Light Grey  
Note: The colour of Rylard Engine Bay Paint Light grey has been matched to Plus Enamel colour "Light Battleship Grey", code 00014. Please refer to our colour card for an indication of the colour.

**PHYSICAL PROPERTIES:**

Supply Viscosity	80seconds/ISO 6 cup/23°C
Supply SG:	0.925-1.175
Theoretical Coverage:	12-15 square metres per litre
VOC Content:	typical 420 grammes per litre
Flash Point / Class / UN No	≥32°C & ≤55°C / III / UN 1263
Pack Size	750ml & 2.5 litre containers
Shelf Life	2 years unopened, stored at UK ambient temperatures.
Health & safety:	Refer to Product Safety Data Sheet before use.

*This information is given in good faith for the guidance of users, but is without warranty or liability. Any queries should be referred to our technical department.*

**Distributed by:**  
Mainline  
2 Sefton Road  
Litherland  
Liverpool L21 7PG  
Tel: 0151 920 6451  
Fax: 0151 920 6452

**Your Local stockist**