



www.RylardBoats.com

Technical Data Sheet

PRODUCT NAME: **RYLAID PAINT CONDITIONER**

CODE NUMBER: 00111

PRODUCT DESCRIPTION: Resin/solvent combination, containing Linseed Oil, formulated for addition to Rylard plus enamel to ensure correct flow and gloss are achieved when humidity/temperature conditions are not ideal.

PERFORMANCE/USE: At certain times of the year, or under certain applications conditions, the temperature or humidity conditions prevailing when **Rylard** Boat Paint or Varnish is applied may affect the flow, levelling or gloss of the applied coating. For these adverse conditions it is recommended that **RYLAID Paint Conditioner** is added to the gloss or top varnish coat to ensure that the expected high gloss and smooth finish is achieved.

SURFACE PREPARATION: N/A

APPLICATION: **RYLAID** is simply added to the final paint coat at a recommended addition of 5-10% by volume. The mixture should be stirred thoroughly before using. After use, as with any paint or varnish, ensure the can is correctly sealed to prevent solvent evaporation or skinning of the contents. Before using **RYLAID**, please read our painting hints booklet.

DRYING/OVERCOATING: N/A

PHYSICAL PROPERTIES:

Supply Viscosity	45 seconds/ISO 4 cup/23°C
Supply SG	0.88
Colour	Clear Liquid
Theoretical Coverage:	N/A
VOC Content:	510 grammes per litre
Flash Point / Class / UN No	≥32°C & ≤55°C / III / UN 1263
Pack Size	1 litre containers
Shelf Life	24 months unopened, stored at UK ambient temperatures.
Health & safety:	Refer to Product Safety Data Sheet before use.

This information is given in good faith for the guidance of users, but is without warranty or liability. Any queries should be referred to our technical department,

Distributed by:

Mainline
2 Sefton Road
Litherland
Liverpool L21 7PG
Tel: 0151 920 6451
Fax: 0151 920 6452

Your Local Stockist: