



www.RylardBoats.com

Technical Data Sheet

PRODUCT NAME: **WATER TANK COATING**
(to BS 3416; 1991; Type 1; Class A)

CODE NUMBER: 40037

PRODUCT DESCRIPTION: New legislation has resulted in the withdrawal of the Water Research council's approval of bitumen for use in water tanks and equipment for all public services. This will mean that bituminous solutions will not be approved by the WRC but its continuing use on existing bituminised tanks will be permitted under BS 3416. For the majority of private boat owners they will still be able to use bitumen coatings such as Rylard water tank coating (bituminous) to BS 3416.

PERFORMANCE/USE: Used to protect water tanks from damage and corrosion.

SURFACE PREPARATION: **Previously painted surfaces:** Ensure existing coating is sound and has full adhesion. Scrape off any areas of flaking and feather back edges with coarse sand paper. Ensure surface is clean and free from dust/dirt.

APPLICATION: Apply 2-3 full coats by brush
Minimum application temperature: 10°C

DRYING/OVERCOATING: Touch Dry(10°C) 6-8 hours
Hard Dry/Overcoating(10°C) 24 hours

PHYSICAL PROPERTIES:

Supply Viscosity	50 seconds/ISO 6 cup /23°C
Supply SG	0.92
Theoretical Coverage:	4 square metres per litre per coat
VOC Content:	400 grammes per litre
Thinner/Cleaner	White Spirit
Flash Point / Class / UN No	≥32°C & ≤55°C / III / UN 1263
Pack Size	750ml and 2.5 litre containers
Shelf Life	12 months unopened, stored at UK ambient temperatures.
Health & safety:	Refer to Product Safety Data Sheet before use.

This information is given in good faith for the guidance of users, but is without warranty or liability. Any queries should be referred to our technical department,

Distributed by:
Mainline
2 Sefton Road
Litherland
Liverpool L21 7PG
Tel: 0151 920 6451
Fax: 0151 920 6452

Your Local Stockist: