



POLYTROL®


COLOUR BACK!

USAGE

- Renews gelcoat and plastic on for example car bumpers, boats, garden furniture etc.
- Regenerates stone, marble, tiles, slates, terracotta etc.
- Restores the lustre on aluminium, chrome, bronze, brass and other metals.
- Gives back the glow to paint and varnishes.

PROPERTIES

- POLYTROL® gives a new glow and returns the colour to surfaces deteriorated by weather.
- Penetrates deeply without creating a film, no risk of peeling.
- Returns the original appearance immediately.
- Long lasting result.



APPLICATION

- The surface must be clean, free from grease and always dry.
- POLYTROL® should not be applied on hot surfaces, in direct sunlight or on large areas. This is to avoid uncontrolled drying.
- Apply plenty of POLYTROL® with a soft brush. Make sure the oil is evenly distributed on the whole surface. Move the oil from less absorbing to more absorbing areas if the surface is not absorbing evenly.
- Remove all product after 5-10 min if the surface is not dry. Use a paper towel or rag that does not leave fluff. After drying, a second application may help obtain a better result.
- Polish gently to obtain a shinier surface.

COVERAGE RATE	APPLICATION TOOLS	TEMPERATURE FOR APPLICATION	DRYING TIME	CLEAN UP
18 m ² /l		+35°C +5°C	10-20 mins BEFORE USE 24 hours	



Owatrol International SL

C/Aragón 179, 5º - 08011 Barcelona - Spain
Tel: +34 934 51 66 04 - Fax: +34 934 52 14 54
info@owatrol.com - www.owatrol.com