



DEKS OLJE #1 & #2

FACT SHEET

Description

Deks Olje #1 matte finish is a deeply penetrating blend of natural oils designed to replace lost oils in wood and prevent moisture ingress. It will stop water from entering the wood whenever damage to any subsequent top coat occurs.

Deks Olje #2 gloss finish is a highly flexible brilliant gloss coating to be used after the wood has been saturated with *Deks Olje #1*. Unlike varnish, *Deks Olje #2* will never peel, crack or blister and is one of the most easily maintained finishes available.

Purpose

To enhance, protect and beautify classic boating wood such as teak, mahogany, etc.

Deks Olje #1, when used on exterior wood should be over coated with *Deks Olje #2* for longer durability.

Drying Time

Deks Olje #1 dries in 6-12 hours. Wait 3 days before over coating with *Deks Olje #2* and apply one coat #2 every 24 hours.

Application

Brush, roller or cloth pad for #1 and a good quality brush for #2.

Container Size

Deks Olje #1 is available in 1, 4 and 10 litres cans.

Deks Olje #2 available in 1 & 4 litre.

Coverage

Deks Olje #1: 1 - 5 sq mtrs per litre depending on the porosity of the timber.

Deks Olje #2: approximately 10 sq mtrs per litre.

Clean-up

Clean equipment and spills with mineral turpentine. Remove dried spatter or spills with a suitable paint remover. Always check for surface compatibility first.

Safety Directions

Follow common sense painting procedures. Wear protective glasses and gloves. If in eyes, flush with plenty of water. If on skin wash with soap and water. If irritation persists, seek medical attention.

Waste Disposal

Used rags saturated with *Deks Olje* may be subject to spontaneous combustion when discarded. Always unfold and allow rags to dry before disposal in accordance with local regulations.