



# Primer Marine

SABA, a strong bond

Solvent based adhesives

MSP sealants

Water based adhesives

Silicone sealants

Foam coatings

Hotmelts

Epoxy products

PU products

Polysulfide products

Primers

Cleaning agents

## Description

SABA Primer Marine is a one-component primer. SABA Primer Marine is very suitable for priming teak deck parts that are to be sealed with SABA Sealer 211 C, SABA Seal One HM and SABA Seal One Fast.

## Special properties

- Very good resistance to water
- Applied primer is visible because of black colour
- Short drying time and long open time

## Method of use

Apply with a brush

## Technical data

Base	: chlorine rubber
Viscosity at 23 °C	: approx. 50 mPa.s
Density	: approx. 1010 kg/m <sup>3</sup>
Colour	: black
Solids content	: approx. 31%
Flash point	: below 32° C
Solvents	: n-butyl propionate
Open time	: 30 minutes - 20 hours
Drying time	: approx. 30 minutes
Coverage	: approx. 100 g/m <sup>2</sup>
Clean tools with	: SABA Cleaner 21
Work temperature	: minimum +5 °C
Storage temperature	: minimum 5 °C, maximum +35 °C
Temperature resistance	: -30 °C up to +70 °C
Shelf life	: 18 months in unopened packing

## Order information

Packing	tin
Content	500 ml

Colour	<b>black</b>
Article No.	100672

## Safety recommendations

See the corresponding material safety data sheet.



## SABA Dinxperlo BV

Industriestraat 3, NL-7091 DC Dinxperlo, Postbus 3, NL-7090 AA Dinxperlo, the Netherlands,  
Tel +31 (0)315 658999, Fax +31 (0)315 653207, E-mail info@saba.nl, Internet www.saba.nl

Our recommendations and instructions for use are based on the present status of know-how and technique. Clients and users should evaluate our products by themselves, with regard to utilization and requirements of their own choice. We shall take no responsibility in case our products are not being used subject to our recommendations and/or instructions for use. Furthermore, General Terms and Conditions of the Dutch Association "Nederlandse Vereniging van Rubber en Kunststoffabrikanten of November 1, 1992", will apply to our recommendations, instructions for use and the delivery of our products.

Version number: 2006/07