



Sealtack Transparent

SABA, a strong bond

Solvent based adhesives

MSP sealants

Water based adhesives

Silicone sealants

Foam coatings

Hotmelts

Epoxy products

PU products

Polysulfide products

Primers

Cleaning agents

Description

SABA Sealtack Transparent is a one-component sealant. SABA Sealtack Transparent is especially appropriate for transparent elastic bonding and sealing.

Special properties

- Transparent
- Free of isocyanates
- Good ageing resistance
- No discolouring of the sealant

Method of use

Surfaces have to be dry, and free from dust and grease. After applying the sealant, please level with a spatula.

Technical data

Basis	: MS-Polymer, moisture curing
Density	: approx. 1030 kg/m ³
Solids content	: approx. 100%
Skin time	: approx. 10 minutes at 23 °C / 75% rh
Cure rate	: approx. 3 mm/24 hrs at 23 °C / 75% rh
Volume shrinkage	: approx. 4% (DIN 52451)
Hardness Shore A	: approx. 35 (DIN 53505)
Modulus at 100%	: 0,6 MPa
Tensile strength	: 1,3 MPa
Elongation at break	: 220%
Work temperature	: minimum + 5 °C, maximum + 35 °C
Storage temperature	: minimum + 5 °C, maximum + 35 °C
Temperature resistance	: approx. from -40 °C up to 100 °C
Shelf life	: 6 months in unopened packaging

Dumbbell test (DIN 53504)

Order information

Packing	cartridge
Content	290 ml

Colour	transparent
Article No.	100680

Safety recommendations

See the corresponding material safety data sheet.



SABA Dinxperlo BV

Industriestraat 3, NL-7091 DC Dinxperlo, PO Box 3, NL-7090 AA Dinxperlo, the Netherlands, Tel +31 (0) 315 658999, Fax +31 (0) 315 653207, E-mail info@saba.nl, Internet www.saba.nl.

Our application instructions and technical advice are based on our actual level of knowledge. We cannot accept any liability for conclusions and recommendations resulting from these. Buyers and/or users should judge the suitability of our products for any envisaged application by preliminary testing. The general terms and conditions for the members of the "Nederlandse Vereniging van Rubber- en Kunststoffabrikanten (NVR)" apply on all our deliveries.

Version number:2005/08