

Epifanes Easy-Flow

Multi purpose additive for use in one-component half-synthetic paints and primers

Type	Air-drying
Base	Selection of natural oils
Properties	A multi-purpose additive or stand alone coating based on a selection of natural oils.
Colour	Amber clear
Gloss	Not applicable
Density	0,86kg./dm ³
Viscosity	15 ± 2 seconds Din Cup 4 mm.
Solids Contents	60 ± 2 %
VOC - level	344 gr./liter
Packing	500ml. - 1000ml. - 5000ml.
Shelf life	In closed container stored in a dark and dry location between 5 - 25°C: 3 years

Recommended use

On steel Rust prevention: Before applying Easy-Flow first remove all loose rust. Prevents rust and has the ability to penetrate existing thin layers of rust impregnating the steel surface. After 12-24 hours drying time, the surface can be recoated with the first coat of a rust preventing system like Werdol Metalprimer, to which 5-10% Epifanes Easy-Flow is added.

On wood Wood Sealer: Epifanes Easy-Flow can be applied full strength onto bare wood as an impregnating wood sealer. In addition, Epifanes Easy-Flow can be added to a wood primer, such as Werdol Woodprimer, up to 25% as a substitute for brush thinner. This will provide better protection to the wood, will improve adhesion and produces an excellent base for the subsequent primer or paint system. Prior to wood application, ensure that the wood is dry, sanded and free of contamination.

As paint additive Flow enhancer / Enriching agent: Epifanes Easy-Flow can be added to all conventional single part and half-synthetic paints and varnishes to improve the flowing characteristics in any conditions less than ideal. Ideally suited for paint or varnish application in cold or extra hot conditions. Recommended percentage is between 5%-10% in volume. This addition will extend the wet edge time, reducing the possibility of laps or brush marks.

Product notes

Epifanes Easy-Flow dries initially with a surface tack. This means that the layer is slightly tacky. This creates a very good adhesion for subsequent paint or primer coats. Unlike other known similar additives Epifanes Easy-Flow shows no tendency to yellowing and is therefore the ideal additive for use in white and bright coloured paints.

Although the facts and suggestions in this product information sheet are based on our own research and field experiences and are believed reliable, we cannot simply be held responsible for performance or results obtained through the use of this product. Ineffectiveness or other unintended consequences may result, because of such factors as weather, conditions, presence or other materials or the manner of preparation, use or application all of which are beyond W. Heeren & Zoon's control. All such risks are assumed by user.

DISCLAIMER OF WARRANTIES. Seller makes no express warranties.

THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. In the event a warranty is created by law, buyer's EXCLUSIVE REMEDY shall be the replacement of any defective product. No other remedy (including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss) shall be available to buyer.

January 2013